

# MNDOT ADA INTERSECTION DETAILS STANDARD LEGEND

REMOVE ALL UNNECESSARY SYMBOLS

Microstation file is available on the ADA Tools website. Don't use all symbols for all projects. Delete any inapplicable symbols from the legend.

Control Points at Gutter Flow Line (not at Top Back of Curb); Truncated Domes; Concrete Curb & Gutter; Curb Height; hatched Landing Areas; Ramp slope ranges; and Drainage Flow Arrows will be used on all projects.



LEGEND	
	INPLACE SIGNAL POLE
	PROPOSED SIGNAL POLE
	PEDESTRIAN PUSH BUTTON STATION
	PEDESTRIAN PUSH BUTTON
	INPLACE PEDESTAL POLE
	PROPOSED PEDESTAL POLE
	PROPOSED SIGNAL CABINET
	EXISTING CABINETS (SCALE TO SIZE)
	CONTROL POINTS AT GUTTER FLOW LINE
	TRUNCATED DOMES (SEE STANDARD PLATE 7038)
	CONSTRUCT CONCRETE CURB & GUTTER
	BITUMINOUS TREATMENT-SEE TABULATIONS
	CURB HEIGHT
	LANDING AREA - 4' X 4' MIN. DIMENSIONS AND MAX 2.0% SLOPE IN ALL DIRECTIONS
	INDICATES PEDESTRIAN RAMP - SLOPE SHALL BE BETWEEN 5.0% MINIMUM AND 8.3% MAXIMUM IN THE DIRECTION SHOWN AND CROSS SLOPE SHALL NOT EXCEED 2.0%
	INDICATES PEDESTRIAN RAMP - SLOPE SHALL BE GREATER THAN 2.0% AND LESS THAN 5.0% IN THE DIRECTION SHOWN AND CROSS SLOPE SHALL NOT EXCEED 2.0%
	DRAINAGE FLOW ARROW
	TRANSITION PANEL(S) - TO BE USED FOR TRANSITIONING THE CROSS-SLOPE OF A RAMP TO THE EXISTING WALK CROSS-SLOPE. RATE OF TRANSITION SHOULD BE 0.5% PER 1 LINEAR FOOT OF WALK.